

NX-P1200NV/P1300NU

5W VHF/UHF DIGITAL & ANALOG PORTABLE RADIOS

If you are thinking of harnessing our renowned NXDN digital protocol to enhance business efficiency or FM analog for its simplicity, KENWOOD ProTalk Digital NX-P1200NV and NX-P1300NU portable business radios have you covered. With mixed-mode operation to ensure seamless integration with legacy radios while smoothing the onward migration path to digital. But whatever your specific needs, audio quality is what determines clear voice communications – which is why KENWOOD radios are used under the most grueling conditions. Thanks to our extensive experience with professional systems, reliability is second to none. So whatever your radio requirements, KENWOOD ProTalk Digital NX-P1200NV and NX-P1300NU radios offer a single platform that's right for you. It's business done right!

Note: Offers the ability to extend coverage with optional repeater (see NXR-710-810 for more information).

NXDN® **FleetSync**®



Switchable Digital and Analog Dual Modes (Digital capable models)

COMPATIBLE WITH DIGITAL AND ANALOG

The NX-P1000 portable radio allows the combination of analog and digital channels in the same zone. This gives you the ability to easily migrate to digital at your own pace, or operate more effectively in a mixed environment where groups of users have different needs or solutions.

NXDN DIGITAL AIR INTERFACE

NEXEDGE radios employ NXDN, an FDMA digital air interface with AMBE+2™ voice coding technology, with forward error correction and unique filtering to obtain superior coverage even at weak RF signal strengths.

ENHANCED AUDIO QUALITY

Based on decades of experience with professional and high quality audio products, the NX-P1000 can be customized to deliver the best digital audio to business radio users with various language backgrounds.

DIGITAL TECHNOLOGY PROVIDES SUPERIOR CLARITY IN EXTENDED COVERAGE

As RF signal strength weakens with distance, analog reception becomes increasingly noisy. NEXEDGE - NXDN digital modulation technology improves audio recovery in fringe areas, thereby "effectively" increasing the usable coverage compared to analog.

Simple Yet Tough

TOUGH & WATER RESISTANT *2

Built to take rough treatment in stride, the NX-P1000 has passed the demanding IP54/55 dust and water intrusion tests – both with and without the KMC-45 optional speaker microphone. It also meets or exceeds 11 stringent MIL-STD 8 10 C/D/E/F/G environmental standards, including "driven rain".

POWERFUL YET NATURAL SOUND OUTPUT

AMBE+2™ vocoder for natural audio with minimum delay; BTL audio amplifier for powerful 1-watt output.

Customize and Deploy

SECOND PTT

Make use of the Second PTT for giving different instructions to different staff as the radio allows the use of main channel plus another channel*1.

SELECTABLE 7-COLOR LED

A large 7-colour LED indicator on the top panel illuminates to notify multi-status functions. *1

CLONING

Customize the radio programming one time and use the optional Cloning Cable to rapidly program groups of ProTalk radios with the same settings.

Secure

Confidentiality in radio communications is a KENWOOD priority, and helping to maintain a high level of security in analog mode is a 16-code voice inversion scrambler, while robust NXDN Digital 15 Bit encryption is available in digital mode.

Other Features

- Voice Announcement • SCAN • VOX / Semi-VOX (headset required) *1
- Button Lock • Time-out Timer • Battery Saver*1 • Calling Alert • QT / DQT
- Compander • Adjustable Microphone Gain • Low Battery Warning

*1: PC programming required.

*2: All interfaces must be fully sealed with appropriate covers or by designated genuine accessories

Accessories

All accessories may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories.

KNB-45L
2,000mAh/7.4V
Li-Ion Battery Pack



KSC-35SK
Fast Charger
For the KNB-45L/69L
82LCM (3-Hour)



KRA-22/23
VHF/UHF Low Profile
Helical Antenna



KMC-45D
Speaker Microphone



KHS-31C
C-Ring PTT Ear
Hanger Headset



KNB-69L
2,550mAh/7.4V
Li-Ion Battery Pack



KSC-43K
Dual Chemistry
Fast Charger
For the KNB 29N/45L/69L/82LCM



KRA-26/ 27
VHF Helical Antenna
UHF Whip Antenna



KHS-26
Earbud In-line
PTT Headset



KBH-10
Belt Clip



KNB-82LCM
2,000mAh/7.4V, Intrinsically
Safe Li-Ion Battery Pack

KVC-22
DC Vehicular
Charger Adapter



KRA-41/42
VHF/UHF
Stubby Antenna



KHS-27A
D-Ring In-line
PTT Headset



Specifications

General	NX-P1200NV	NX-P1300NU
Pre-set Frequencies	151-159 MHz	451-470 MHz
Max. Channels per Radio	64 channels	
Number of Zones	4 zones	
Max. Channels per Zone	16 channels	
Channel Spacing		
Analog	25" / 12.5 kHz	
Digital	12.5 / 6.25 kHz	
Power Supply	75 VDC ±20 %	
Battery Life (5-5-90)		
KNB-45L (2000mAh)	Approx. 11.5 hours	
KNB-69L (2550mAh)	Approx. 14.5 hours	
Operating Temperature(Radio only)*	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability (-30 to +60°C; +25°C Ref.)	±0.5 ppm	
Antenna Impedance	50 Ω	
Dimensions	(W x H x D) Projections Not Included	
Radio with KNB-45L/82LCM	213 x 484 x 132 in (54 x 123 x 33.5 mm)	
Radio with KNB-69L	213 x 484 x 148 in (54 x 123 x 37.5 mm)	
Weight		
Radio Only	5.64 oz (160 g)	
Radio with KNB-45L/82LCM	9.88 oz (280 g)	
Radio with KNB-69L	10.41 oz (295 g)	
FCC ID	K44501000	K44501001

*125 / 30 kHz in VHF/UHF Bands excluding T-Band are not included in the models sold in the USA or US territories.
*2 Operating temperature specification for a Li-Ion battery is -10°C to +60°C [-14°F to +140°F].

Specifications shown are typical and subject to change without notice, due to advancements in technology. Details and timing of firmware and software updates are subject to change without notice. Analog measurements made per TIA603. Specifications are measured according to applicable standards. All interfaces must be fully sealed with appropriate covers or by designated genuine accessories.

Receiver	NX-P1200NV	NX-P1300NU
Sensitivity		
NXDN® @ 6.25 kHz Digital (3% BER)		0.18 µV
NXDN® @ 12.5 kHz Digital (3% BER)		0.22 µV
Analog @ 12.5/25 kHz (12 dB SINAD)		0.20 µV / 0.24 µV
Selectivity		
Analog @ 12.5 / 25 kHz		68 dB / 74 dB
Intermodulation Distortion		70 dB
Spurious Rejection		70 dB
Audio Distortion		7%
Audio Output Power		1 W / 12 Ω (Internal Output) 500 mW / 8 Ω (External Output)
Transmitter	NX-P1200NV	NX-P1300NU
RF Power Output* ² (High / Low)		5 W / 4 W / 1 W
Spurious Emission		-70 dB
FM Hum & Noise		
Analog @ 12.5 / 25 kHz		40 dB / 45 dB
Audio Distortion		2%
Emission Designator		16K0F3E, ¹ 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D

FleetSync® is a registered trademark of JVCケンウッド Corporation in the United States and/or other countries. NXDN® is a trademark of JVCケンウッド Corporation and Icom Inc. NEXEDGE® is a registered trademark of JVCケンウッド Corporation. ProTalk® is a registered trademark of JVCケンウッド Corporation. AMBE+2™ is a trademark of Digital Voice Systems Inc. All other trademarks are the property of their respective holders.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	5001/Procedure I	5002/Procedure I, II	5003/Procedure I, II	5004/Procedure I, II	5005/Procedure I, II
High Temperature	5011/Procedure I, II	5012/Procedure I, II	5013/Procedure I, II	5014/Procedure I, II	5015/Procedure I, II
Low Temperature	5021/Procedure I	5022/Procedure I, II	5023/Procedure I, II	5024/Procedure I, II	5025/Procedure I, II
Temperature Shock	5031/Procedure I	5032/Procedure I	5033/Procedure I	5034/Procedure I, II	5035/Procedure I
Solar Radiation	5051/Procedure I	5052/Procedure I	5053/Procedure I	5054/Procedure I	5055/Procedure I
Rain*	5061/Procedure I, II	5062/Procedure I, II	5063/Procedure I, II	5064/Procedure I, III	5065/Procedure I, III
Humidity	5071/Procedure I, II	5072/Procedure II, III	5073/Procedure II, III	5074	5075/Procedure II
Salt Fog	5091/Procedure I	5092/Procedure I	5093/Procedure I	5094	5095
Dust	5101/Procedure I	5102/Procedure I	5103/Procedure I	5104/Procedure I, III	5105/Procedure I
Vibration	5142/Procedure VIII, X	5143/Procedure I	5144/Procedure I	5145/Procedure I	5146/Procedure I
Shock	5162/Procedure I, II, V	5163/Procedure I, IV	5164/Procedure I, IV	5165/Procedure I, IV	5166/Procedure I, IV

International Protection Standard

Dust & Water Protection*

IP54/55*

*To meet IP54/55, the 2-pin connector cover has to be connected on the radio or the locking bracket has to be attached to the external speaker microphone.

JVCケンウッド USA Corporation
Communications Sector Headquarters
1440 Corporate Drive | Irving, TX 75038

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

JVCケンウッド Canada Inc.
Sede central y distribución canadiense
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca

KENWOOD Communications
Global Website



comms.kenwood.com



ISO9001 Registered
Communications Systems Business Unit
JVCケンウッド Corporation
ADS#03420 Print in USA.